

# INNOLINQ





# INNOLINQ

Industrial plugs and sockets for sustainable, safe and high-performance connections "Made in Germany." All products are lead-free, fully recyclable and already compliant with upcoming EU REACH and RoHS regulations. This allows us to combine maximum environmental compatibility with top performance. Every detail is optimized for industrial requirements: ergonomic design, high stability, larger contact surfaces and optimized plugging and pulling forces ensure safe, durable and efficient connections – even under extreme loads. The 16A and 32A variants come standard with QUICK-CONNECT, for fast, convenient and secure conductor connection.



## Resource-saving

Lead-free, fully recyclable and already compliant with upcoming REACH and RoHS regulations.



## VDE-certified

Guarantees tested, safe and standards-compliant products; additionally verified in our own testing laboratory.



## Secure connection

QUICK-CONNECT ensures a controlled conductor connection, resistant to vibrations and temperature fluctuations, visibly and audibly locked.



## Improved ergonomics

Optimized contours for easy handling, secure grip and effortless opening of the hinged cover.



## Extremely robust

Manufactured from durable, recyclable materials for maximum longevity.



## Screwless installation

No tools required thanks to QUICK-CONNECT for 16A and 32A – fast, convenient and reliable.





**Wall mounting socket outlet INNOLINQ 16A/32A IP54**

- Enclosure dimension: 92 x 94 mm
- Screwless terminals
- The cable entry is one at top open and one at bottom and one rear side closed
- Protection degree IP54
- Contains no lead

**QUICK CONNECT**  
**KONTEX ULTRA**

Ampere	Poles	Volt	Bals Art.-No.	Qty
16	3	230	11895	10
16	4	400	110670	10
16	5	400	110624	10
32	3	230	110646	10
32	4	400	110658	10
32	5	400	110635	10



**Wall mounting socket outlet INNOLINQ 16A/32A IP67/IP69**

- Enclosure dimension: 115x110
- Screwless terminals
- The cable entry is one M25 at top open
- Protection degree IP67/IP69
- Contains no lead

**QUICK CONNECT**  
**KONTEX ULTRA**

Ampere	Polzahl	Volt	Bals Art.-Nr.	Stück
16	3	230	112013	10
16	4	400	112014	10
16	5	400	112015	10
32	3	230	112016	10
32	4	400	112017	10
32	5	400	112018	10



**Surface mounting socket outlet INNOLINQ 16A/32A IP54**

- Screwless terminals
- Straight
- Flange 75 x 75 mm
- Drill hole spacing 60 x 60 mm
- Protection degree IP54
- Contains no lead

**QUICK CONNECT**  
**KONTEX ULTRA**

Ampere	Poles	Volt	Bals Art.-No.	Qty
16	3	230	136861	10
16	4	400	136931	10
16	5	400	1320011	10
32	3	230	137031	10
32	4	400	137101	10
32	5	400	1320021	10



**Surface mounting socket outlet INNOLINQ 16A/32A IP54**

- Screwless terminals
- Inclined
- Flange 85 x 85 mm
- Drill hole spacing 70 x 70 mm
- Protection degree IP54
- Contains no lead

**QUICK CONNECT**  
**KONTEX ULTRA**

Ampere	Poles	Volt	Bals Art.-No.	Qty
16	3	230	127491	10
16	4	400	127531	10
16	5	400	127571	10
32	3	230	127611	10
32	4	400	127641	10
32	5	400	127681	10



**Surface mounting socket outlet INNOLINQ 16A/32A IP67/IP69**

- Screwless terminals
- Straight
- Flange 75 x 75 mm
- Drill hole spacing 60 x 60 mm
- Protection degree IP67/IP69
- Contains no lead

 QUICK CONNECT  
 KONTEX ULTRA

Ampere	Poles	Volt	Bals Art.-No.	Qty
16	3	230	<b>137341</b>	10
16	4	400	<b>137391</b>	10
16	5	400	<b>137451</b>	10
32	3	230	<b>137501</b>	10
32	4	400	<b>137561</b>	10
32	5	400	<b>137621</b>	10



**Surface mounting socket outlet INNOLINQ 16A/32A IP67/IP69**

- Screwless terminals
- Inclined
- Flange 85 x 85 mm
- Drill hole spacing 70 x 70 mm
- Protection degree IP67/IP69
- Contains no lead

 QUICK CONNECT  
 KONTEX ULTRA

Ampere	Poles	Volt	Bals Art.-No.	Qty
16	3	230	<b>128131</b>	10
16	4	400	<b>128141</b>	10
16	5	400	<b>128171</b>	10
32	3	230	<b>128191</b>	10
32	4	400	<b>128211</b>	10
32	5	400	<b>128241</b>	10



**Plug INNOLINQ 16A/32A IP54**

- Screwless terminals
- Screwless enclosure connection
- Special gland, simultaneous cable gland and seal
- Protection degree IP54
- Contains no lead

- QUICK CONNECT**
- KONTEX ULTRA**
- MULTI GRIP**

Ampere	Poles	Volt	Bals Art.-No.	Qty
16	3	230	<b>211</b>	10
16	4	400	<b>215</b>	10
16	5	400	<b>200</b>	10
32	3	230	<b>2114</b>	10
32	4	400	<b>2118</b>	10
32	5	400	<b>201</b>	10



**Plug INNOLINQ 63A IP44**

- Improved ergonomics, thanks to the new INNOLINQ design
- Nickel-plated contacts
- Special gland, simultaneous cable gland and seal
- Screwless enclosure connection
- Protection degree IP44
- Contains no lead

- KONTEX ULTRA**
- MULTI GRIP**

Ampere	Poles	Volt	Bals Art.-No.	Qty
63	3	230	<b>2104-1</b>	5
63	4	400	<b>2151-1</b>	5
63	5	400	<b>2155-1</b>	5



**Plug INNOLINQ 63A/125A IP67/IP69**

- Improved ergonomics, thanks to the new INNOLINQ design
- Nickel-plated contacts
- Special gland, simultaneous cable gland and seal
- Screwless enclosure connection
- Protection degree IP67/IP69
- with recyclable SUSTAINABLE-GRIP
- Contains no lead

- KONTEX ULTRA**
- SUSTAINABLE GRIP**
- MULTI GRIP**

Ampere	Poles	Volt	Bals Art.-No.	Qty
63	3	230	<b>2181-1</b>	5
63	4	400	<b>2185-1</b>	5
63	5	400	<b>2189-1</b>	5
125	3	230	<b>2191-1</b>	5
125	4	400	<b>2195-1</b>	5
125	5	400	<b>2199-1</b>	5



**Wall mounting appliance inlet INNOLINQ 16A/32A IP54**

- Enclosure dimension: 92 x 94 mm
- Screwless terminals
- The cable entry is one at top open and one at bottom and one rear side closed
- Protection degree IP44
- Contains no lead

- QUICK CONNECT**
- KONTEX ULTRA**

Ampere	Poles	Volt	Bals Art.-No.	Qty
16	4	400	<b>24714</b>	10
16	5	400	<b>24675</b>	10
32	3	230	<b>24691</b>	10
32	4	400	<b>24703</b>	10
32	5	400	<b>24661</b>	10



### Connector INNOLINQ 16A/32A IP54

- Screwless terminals
- Special gland, simultaneous cable gland and seal
- Screwless enclosure connection, self locking
- Protection degree IP54
- Contains no lead

- QUICK CONNECT
- KONTEX ULTRA
- MULTI GRIP

Ampere	Poles	Volt	Bals Art.-No.	Qty
16	3	230	<u>311</u>	10
16	4	400	<u>315</u>	10
16	5	400	<u>300</u>	10
32	3	230	<u>3114</u>	10
32	4	400	<u>3118</u>	10
32	5	400	<u>301</u>	10



### Connector INNOLINQ 63A IP44

- Improved ergonomics, thanks to the new INNOLINQ design
- Nickel-plated contacts
- Special gland, simultaneous cable gland and seal
- Screwless enclosure connection
- Protection degree IP44
- Contains no lead

- KONTEX ULTRA
- MULTI GRIP

Ampere	Poles	Volt	Bals Art.-No.	Qty
63	3	230	<u>3104</u>	5
63	4	400	<u>3151</u>	5
63	5	400	<u>3112</u>	5



### Connector INNOLINQ 63A/125A IP67/IP69

- Improved ergonomics, thanks to the new INNOLINQ design
- Nickel-plated contacts
- Special gland, simultaneous cable gland and seal
- Screwless enclosure connection
- Protection degree IP67/IP69
- with recyclable SUSTAINABLE-GRIP
- Contains no lead

- KONTEX ULTRA
- SUSTAINABLE GRIP
- MULTI GRIP

Ampere	Poles	Volt	Bals Art.-No.	Qty
63	3	230	<u>3181-1</u>	5
63	4	400	<u>3185-1</u>	5
63	5	400	<u>3124-1</u>	5
125	3	230	<u>3191-1</u>	5
125	4	400	<u>3195-1</u>	5
125	5	400	<u>3199-1</u>	5

 made  
 in  
 Germany



Simply. Well. Connected.

Bals Elektrotechnik GmbH & Co. KG  
D-57399 Kirchhundem-Albaum  
Phone: +49 27 23/771-0  
Fax: +49 27 23/771-177/178  
E-mail: [info@bals.com](mailto:info@bals.com)  
Internet: [www.bals.com](http://www.bals.com)